



# EntryGuard™ Biometric Waterproof Mobile Reader (TA-HH) Networkable & Addressable



## Waterproof Mobile Reader A variety of models are available.

FaceKey's EntryGuard™ mobile reader identifies the user and records who, when and where the reader is used. The TA-HH is a unique portable fingerprint attendance terminal with a rubber coating. The unit is waterproof and dustproof with efficacy rated at the IP65 protection grade. The TA-HH is shockproof up to one meter above the ground, if dropped. The unit has a handle at the top.

The TA-HH mobile reader with its low power consumption and design delivers long standby and usage time. The unit comes with a long life lithium-ion battery.

### High Capacity Feature

The standard fingerprint capacity of the unit is 5,000 and can be ordered with a capacity of 10,000 templates. The TA-HH is available with generic or Mifare card readers.

### Applications

The EntryGuard™ mobile TA-HH lends itself to a variety of applications. For example: time and attendance systems, mustering drills or custom applications.

The mobile device is convenient for attendance in industries such as construction, mining and agriculture.

### Compatibility:

The fingerprints enrolled by the TA-HH fingerprint reader can be shared with other EntryGuard™ devices. The mobile models are network based and utilize the same software common to the entire EntryGuard™ family of products.

### Expandability

The Linux OS offers more flexibility for integrators to develop new and custom applications and features.

\* HID card format H10301 26 bit

### Benefits and Options

- OS Linux
- Equipped with optical fingerprint reader and keypad
- 16-Key Keypad 0-9 and 6 function keys
- 8 Programmable function keys/hot keys
- Acknowledgment of acceptance: LED indicator, display indication and voice reply
- Centralized enrollment available with Management Software (optional)
- Database: Access, SQL and others available with FaceKey™ Management Software package
- SMS (Short Message System) individual and public
- Daylight savings time (DLST)
- T9 input for Alpha input at keypad
- 3.5" TFT display

### Technical Specifications:

- Connectivity: TCP/IP, RS232 & USB host
- Optional: WiFi, GPRS or 3G(WCDMA)
- Fingerprint Capacity: 5,000 (Optional 10K)
- Card Capacity: 30,000
- Transaction Storage: 200,000 activities
- Identification Time: <=1s
- FAR: <=0.0001%
- FRR: <=1%
- Power Supply: AC-110-230/ DC 5V 2A
- Battery: 7600 mAh Lithium-ion
- Battery Life Usage: 4 hours
- Battery Life Standby: 3 days
- Dimensions: 9 X 9.25 X 5 (H X W X D)
- Temperature Range: 32°-113°F (0°-45°C)
- Humidity Range: 20%-80%
- Net weight (with battery): 468g (1.2 lbs.)
- Protection Grade: IP65

## FaceKey™ Corporation

900 NE Loop 410, Suite D401  
San Antonio, TX 78209  
210-826-8811

[www.facekey.com](http://www.facekey.com)

Email: [info@facekey.com](mailto:info@facekey.com)

Model #	FaceKey Part #
TA-HH+MIL	8022048
TA-HH+EM=WIFI	8022049
TA-HH+MIL+WIFI	8022050
TA-HH+EM+GRPS	8022051
TA-HH+NIL+GRPS	8022052
TA-HH+WIFI	8022053
TA-HH+HID+WIFI*	8022054
TA-HH+EM	8022055
TA-HH+HID+GRPS*	8022057
TA-HH	8022058