

**Your Face is your Key**  
**Access Control or Time Clock**

Users of the FKFR-3K can clock in/out at work or access their work place.

The unit is designed for indoor use only. The internal cameras, digital and IR, auto adjust for background lighting.

**Three Factor ID is Available:** The design permits the FKFR-3K to operate in one, two or three factor mode. The FKFR-3K has four ID methods which affords 10 ID combinations. The ID methods are: face, PIN, password or card reader. The ID methods can be presented in any order.

The FaceKey™ FKFR-3K Station can function as a standalone device or multiple units can be connected over a network. Each unit is TCP/IP addressable and has a unique MAC address visible on the internet.

The FKFR-3K when used for access control is a full featured access control device, see “Benefits and Features”. The FKFR-3Kunit is available with a RFID card reader (Generic or Mifare). The FKFR-3K when used as a time clock has the same features except the unit does not unlock doors.

**Software:** The FaceKey™ Management Software automatically synchronizes all FaceKey devices with the network and manages the face templates. If the network fails, the units will continue to operate and collect data which will be uploaded when communication with the network is reestablished. The FKFR-3K can connect to FaceKey’s web based (cloud) TimeKeeper Time and Attendance System.

**Scalable:** The FaceKey™ Management Software database supports an unlimited number of devices and users. Each Standard FKFR-3K has 3,000 face templates and 50,000 ID cards if a card reader is imbedded. Call FaceKey to discuss.

### FaceKey™ Corporation

900 NE Loop 410, Suite D401  
 San Antonio, TX 78209  
 210-826-8811

[www.facekey.com](http://www.facekey.com)

Email: [info@facekey.com](mailto:info@facekey.com)

Standard FKFR-3K model and part nos. Contact FaceKey for special order products. (Optional WIFI Available)



#### **Benefits and Features:**

- Easy installation
- Connects directly to local area network
- Red and green status indicators
- 2.8” touch screen (TFT) display
- Auto correction contrast & brightness
- Face recognition
- Virtual keyboard and keypad
- Three factor ID:
  - Face+PW+card (example)
- Professional access control features
  - 50 Time zones
  - 10 Unlock combinations
  - 5 Groups
  - Anti-pass back
  - Tamper switch
  - Alarm output
  - Door sensor input
  - Exit request input
  - USB Port to download/upload
- Holiday schedule
- Egress/Ingress function (schedule door to open/lock)
- Acknowledgment of acceptance: LED indicator, display indication and voice reply
- SMS (Short Message System)

#### **Technical Specifications:**

- Identification (Face)
  - Time <=1s
- Transaction Capacity:
  - Event Log 100,000 events
  - Faces 3000
- Connectivity: TCP/IP, USB host, WIFI
- Wiegand output (26 or 34 bit standard)
- Dimensions: 4.125 (L) X 6.3 (W) X 1.4 (D) in.
- Voltage input: 12 VDC (supply not included)
- Indoor only
- Temperature range: 32°- 113°F (0°-45°C)

Description	Model #	Part #
Standard	FKFR-3K	8033170