



Shepherd Elite™ FKFP-PRO3-4A FKFR-PRO3-4B

NEW INSTALLATION OR RETROFIT

PRO3 Series

Face/Fingerprint or Face only The New Standard for Access Control!

The PRO3 series identifies an authorized user by their face and fingerprints or their face only. There are two versions:

- **FKFP-PRO3-4A** – with Face, Fingerprint, RFID Card, and Password.
- **FKFR-PRO3-4B** – with Face, RFID Card, and Password.

The **RFID cards** are **MIFARE (13.56 MHz)** and **EM (125 kHz)**.

Advanced thermal-imaging technology, in combination with special anti-spoofing algorithms, detects and rejects photos of faces and fingerprints. Identification is fast, accurate, and works at distances of up to 6.5 feet. The device is rated IP65.

The PRO3 is suitable for both a single door or multinational installations. Who benefits? The list is long: hospitals, factories, schools, companies and government.

Overview: The PRO3 series is a powerful, full featured solution:

- Stores up to 6000 face templates, and 8000 fingerprint templates.
- Supports these RFID cards: 13.56 MHz Mifare, 125 kHz EM card readers.
- Operates on your network and each device is TCP/IP addressable with a unique MAC address visible on the internet.
- All communications and templates are encrypted with 128-bit technology.

Software: The PRO3 series runs with **Shepherd Elite** or **Shepherd Hybrid** software, including a **Device Management 2.0** tool for easy setup and operation.

Warranty: Comes with a 2-year warranty.
Call FaceKey™ for pricing and other options.

Description	Model #	Part #
W/EM Cd.	FKFP-PRO3-4A+EM+WIFI	8033190
W/EM Cd, Face only.	FKFR-PRO3-4B+EM+WIFI	8033191
W/Mifare Cd.	FKFP-PRO3-4A+MIF+WIFI	8033192
W/Mifare Cd, Face only.	FKFR-PRO3-4B+MIF+WIFI	8033194

FaceKey™ Corporation

900 NE Loop 410, Suite D401
San Antonio, TX 78209
210-826-8811 sales@facekev.com
www.facekev.com

Revised: 04/16/25



Benefits and Features:

- Easy installation.
- Connects directly to local area network. (WIFI option available).
- 4" Touch Screen.
- Auto correction, contrast & brightness. Face, Fingerprint, Card, PIN.
- Virtual keyboard & keypad.
- Three factor ID.
- Professional access control features.
- Daylight savings time.
- Holiday schedule.
- Acknowledgment of acceptance: display indication and voice reply.
- Auxiliary input.
- Proximity cards: 13.56 MHz IC card (Mifare), 125 kHz EM cards (EM format).
- Certifications: ISO14001, ISO9001, CE, FCC.
- IP65 Rating outside use.

Technical Specifications:

- Linux OS.
- Dimensions: 6.88 (L) X 3.3 (W) X .85 (D) in.
- Voltage input: 12 VDC (power supply not included).
- Temperature operating range: -5°C ~ 45°C (23°F ~ 113°F).
- Event Log 200,000 events.
- Faces 6000.
- Fingerprint 8000.
- Cards 8000.
- Identification Face FAR ≤ 0.01%.
- Identification Fingerprint FAR ≤ 0.0001% (PRO3-4A only).
- Connectivity: TCP/IP, RS485, Wiegand Input/Output.